



Setting the standards

Betonit™

Betonit

SURFACE PREPARATION & PROTECTION

The secret to a good finish is good substrate preparation. Betonit has developed a variety of excellent products to choose from to ensure a quality substrate.

ALSO AVAILABLE:

TILING PRODUCTS



Betonit's range of tile installation products are known for being synonymous to quality and strictly maintains its product formulations that conform to the requirements set by the American National Standards Institute (ANSI). Certification by a credible and recognized third-party testing institute attests to the consistent quality and superior performance of Betonit products sold in the market.

Altamira Mineral Paint natural architectural finishes

Altamira Mineral Paint is a premium decorative finish suitable for a wide range of architectural designs. It is a cementitious, polymer-modified mixture available in an array of premixed colors. It can be applied on interior and exterior surfaces made of concrete masonry finish, fiber cement board, gypsum board and EPS.


Betonit Products Phils Inc.

 TEL: (632) 932.8806 / (632) 931.3822 • FAX: (632) 875.7173
 sales@betonitproducts.com • www.betonitproducts.com

 PENETRATING STONE
& STUCCO SEALER


Betonit MatteSEAL is a water-based silane-siloxane sealer which provides water repellent properties to mineral substrates. It penetrates and chemically bonds with the surface to seal them against moisture.

applications

- Marble, travertine, limestone & granite with recent properties like sealing, staining, etc.
- Granite or travertine with old sealers present with some stains not seeping into the surface.
- Stucco finish
- Artificial Stone or engineered Stone
- Concrete or Masonry Design

advantages

- Protects against moisture, stains and discoloration
- Strengthens the surface and restores color
- Provides an invisible crystal-like protective finish with some stains not seeping into the surface.
- Excellent protection against water due to deep chemical penetration, not just on the surface
- Resists mold, mildew, dirt, stains, water, etc.
- Easy maintenance cleaning
- Protects natural, color and texture of treated surfaces



APPROXIMATE COVERAGE: 20-40 sqm/4L, double depending on porosity of material

how to use:

SURFACE PREPARATION: Surface to be sealed must be fully cured, clean, dry, and free from any loose material. Remove any old sealers, stains, etc. and allow the surface to dry completely.

- 1 Using a brush, roller or sprayer, apply MatteSEAL in the direction of the grain of the material.
- 2 Repeat if necessary. Do not allow the surface to dry before the next application.
- 3 Allow at least 24 hours before sealing to normal usage. Sealing will take 48 hours for full strength.

NOTES: Test the sealer on a small spot prior to treating the entire surface to ensure compatibility and the desired appearance. The liquid in MatteSEAL will cure and will not affect the color of the surface. • In extreme cases, consult the technical data sheet for detailed application instructions.

Test MatteSEAL on a small spot prior to treating the entire surface to ensure compatibility and the desired appearance.

1. First, remove old sealers with a power washer or use a solvent to remove old sealers.
2. Second, clean the surface with a brush and water to remove any dirt and debris.
3. Third, allow the surface to dry completely before applying MatteSEAL.
4. Fourth, apply MatteSEAL in the direction of the grain of the material.

matte finish keeps the natural look of stone & concrete

GLOSS TOPCOAT is a solvent-based acrylic sealer formulated to provide excellent resistance against salt water spray, UV rays and dirt penetration. It dries quickly and provides a durable finish that enhances the color of the painted surface.

applications

- A durable glossy finish that enhances the color of the surface
- Excellent resistance against water and oil-based stains
- Resists mold, mildew, dirt, stains, water, etc.
- Easy maintenance cleaning
- Excellent leveling
- Fast drying time
- Resistant to black marks and scuffs

Available in 1L and 4L containers

How to use:

- 1 Make sure that the surface is completely clean and free of contaminants.
- 2 When applied on top of Altamira Mineral Paint, make sure paint has fully cured prior to application.
- 3 Recommended application: single pass of brush.
- 4 Apply a second coat when the first coat has sufficiently dried.

NOTES: It is recommended to apply the sealer on a small inconspicuous area before applying it to the whole area.

APPROXIMATE COVERAGE: 20 sqm/4L (2 coats)

* depending on substrate porosity and condition, and method of application

SEMI-GLOSS TOPCOAT is a water-based emulsion sealer composed of resins, polymers, emulsifiers, surfactants and water. It is milky white in appearance but dries clear.

applications

- Use on exterior walls or floors of concrete, terrazzo, quarry tile, etc. (grouted joints and grout lines finish)
- Easy application
- Excellent leveling
- Fast drying time
- Resistant to black marks and scuffs

Available in 4L containers

How to use:

- 1 Make sure that the surface is completely clean and free of contaminants.
- 2 When applied on top of Altamira Mineral Paint, make sure paint has fully cured prior to application.
- 3 Apply 2-4 coats of Semi-Gloss Topcoat, allow at least 30 minutes of drying between each coat. It is important to make sure the finish has dried completely before each additional coat is applied.

NOTES: It is recommended to test the sealer on a small inconspicuous area before applying it to the whole area.

APPROXIMATE COVERAGE: 20 sqm/4L (2 coats)

* depending on substrate porosity and condition, and method of application


 ACRYLIC BASED AND
WATER BASED SEALERS

protect and enhance your finish

