



Betonit Ezyplast is a high quality acrylic solution intended as concrete admixture designed for effective repairs and plastering. It is suitable as a Bonding Aid as well as a Plastering Aid.

applications

PLASTERING AID

Mix with plaster mortar to improve adhesion, tensile, flexural and compressive strengths, and improve elasticity of fresh plaster coat.

BONDING AID

Mix with portland cement to form a bonding slurry coat between old concrete and fresh plaster or skim coat. Also suitable for patching and repair works.

advantages

PLASTERING AID

- Reduces cracking and shrinkage of plaster coat
- Controls water loss in mortar for proper curing
- Increases bonding of plaster coat to masonry wall
- Increases the abrasion resistance of concrete
- Reduces brittleness of concrete.

BONDING AID

- Improves bonding of new to old concrete
- Eliminates the need for concrete surface roughening or scarifying work.

USE PROTECTIVE WEAR



SHAKE WELL BEFORE USING



STORE IN COOL DRY PLACE



SHELF LIFE



APPROXIMATE COVERAGE: 20sqm/4L bottle

How to use:

SURFACE PREPARATION:

- All concrete surfaces must be properly cured before plastering or bedding work commences. Uneven or cracked areas must be properly repaired and exposed bars appropriately cleaned and primed.
- Clean concrete surfaces thoroughly by removing all loosely adhering particles, dirt, oils, paints and other contaminants.
- IMPORTANT - Dampen the substrate before applying the plaster or the bonding slurry.

BONDING AID

1 Mix equal parts of Betonit Ezyplast, Portland cement and plastering sand until a creamy slurry is attained.



PLASTERING AID

1 Mix Betonit Ezyplast with water in a clean container. Use guidelines on mixing ratios.

2 Add solution to cement and sand as replacement for water requirement.

REGULAR STRENGTH



OR HEAVY DUTY



* approximate amounts always check for desired consistency

2 Dampen the substrate. Using a notched trowel or stiff brush, apply a 1-2 mm thin coat of slurry prior to applying thick bed plaster of mortar.

APPLY THICK BED PLASTER OR MORTAR WHILE SLURRY IS STILL TACKY, USUALLY WITHIN 20 MINS.

Wala nang TIKTIK!



BONDING AID



PLASTERING



REPAIR

ACRYLIC LATEX ADMIXTURE
& BONDING AGENT

plastering made easy