



GLOSS TOPCOAT is a solvent-based acrylic sealer formulated to provide excellent resistance against salt water spray, UV rays and dirt penetration. It dries quickly and provides a durable finish that enhances the color of the painted surface.

applications

- A durable glossy finish that enhances the color of painted surfaces.
- Excellent resistance against water and against both water and oil-based stains
- Provides resistance against mild abrasion and skid marks

Available in 1L and 4L containers.

How to use:

- 1 Make sure that the surface is thoroughly clean and free of contaminants.
- 2 When applied on top of Altamira Mineral Paint, make sure paint has fully cured prior to application.



- 3 Recommended application: single pass of brush.
- 4 Apply second coat when the first coat has sufficiently dried.

Note: It is recommended to test the sealer on a small inconspicuous area before applying it to the whole area.

APPROXIMATE COVERAGE: 20 sqm/4L (2 coats)

*depending on substrate porosity and condition, and method of application

SEMI-GLOSS TOPCOAT is a water-based emulsion sealer composed of resins, polymers, emulsifiers, surfactants and water. It is milky white in appearance but dries clear.

applications

Use on resilient walls or floors of concrete, terrazzo, quarry tile, brick, unglazed ceramic and other stone finishes.

- Easy application
- Excellent levelling
- Fast drying time
- Resistant to black marks and scuffs

Available in 4L containers.

How to use:

- 1 Make sure that the surface is thoroughly clean and free of contaminants.
- 2 When applied on top of Altamira Mineral Paint, make sure paint has fully cured prior to application.



- 3 Apply 2-4 coats of Semi-gloss Topcoat. Allow at least 30 minutes of drying between each coat. It is important to make sure the finish has dried completely before each additional coat is applied.

Note: It is recommended to test the sealer on a small inconspicuous area before applying it to the whole area.

APPROXIMATE COVERAGE: 20 sqm/4L (2 coats)

*depending on substrate porosity and condition, and method of application

ACRYLIC-BASED AND
WATER-BASED SEALERS

protect and enhance your finish