



Gloss Topcoat

ALTAMIRA Mineral Paint GLOSS TOPCOAT is a 100% solvent-based acrylic topcoat sealer formulated to provide excellent resistance against salt water spray, U.V. rays and dirt penetration.

It dries quickly and provides a durable glossy finish that enhances the color of the painted surface.

It can slightly darken the color of the painted surface.

Benefits:

- Highly durable
- Excellent resistance against water
- Excellent resistance against both water-based and oil-based stains
- Prevents efflorescence (formation of white residue)
- Excellent resistance against ultraviolet rays
- Provides protection against mild abrasion and skid marks

Application:

1. Make sure that the surface is thoroughly clean and free of contaminants
2. When applied on top of Ryoliitte, make sure that the paint has fully cured prior to application.
3. Recommended application tool: brush
4. It is recommended to test the sealer on a small inconspicuous area before applying it to the whole area.

Drying Time:

Set to touch : 1 minute

Dry hard : 10 minutes

Package size: 1 gallon



Semi-Gloss

PRODUCT INFORMATION SHEET

20130209

DESCRIPTION

Altamira Semi-Gloss is a milky-white and water-based emulsion floor sealer. It is designed to give a long-lasting insignificant gloss to your finishes. It dries quickly and enhances the color of the painted surfaces.

BENEFITS

- Highly durable
- Excellent resistance against water penetration
- Excellent resistance against both water-based and oil-based stains
- Prevents formation of efflorescence
- Excellent resistance against ultraviolet rays
- provides protection against mild abrasion and skid marks

APPLICATION

- Make sure that the surface is thoroughly clean and free of contaminants.
- When applied on top of Altamira Mineral Paint, make sure that the paint has fully cured prior to application
- Additional coats may be necessary for added gloss preferences.
- It is recommended to test the gloss sealer on a small inconspicuous area before applying it to the whole area.

DRYING TIME

In between coats 20 minutes

PACKAGING SIZE

1 gallon