



# PRODUCT INFORMATION

## Product Description

**Betonit Grout Sealer** is a water-based penetrating sealer for cementitious tile grout. It may also be used to seal **plaster, cement mortar, concrete** and **other porous masonry surface**.

By protecting your floors with the new Betonit Grout Sealer, you can improve the appearance of your floors while reducing cleaning time and costs.

## Features

This ready-to-use, water-based formula deeply penetrates and bonds with porous tile, grout or other porous masonry surface to provide:

### Better-looking floors.

- Preserves natural look and color of grout
- Creates an invisible shield that helps protects tile and grout from getting dirty or stained by resisting liquid penetration. Protects against mildew growth on treated surfaces.

### Faster and easier routine cleaning.

Invisible shield helps prevent water-based stains from soaking into the grout, making mopping quick and easy.

### Fresher smelling floors.

Protects against odor-causing mildew on treated surfaces.

### Easy to Apply

- Can be applied 12 hours after grouting.
- It may also be applied to damp or wet surfaces.

### How it Works?

- Sealer lines the pores of the surface without filling or blocking it, to prevent liquid absorption while allowing gas permeability.
- Also, coats the surface to repel water

### Limitations:

- This product is not a substitute for waterproofing
- Do not use to seal surfaces such as roofdecks, basements, ceilings, and pools.

## Consumption

- *For tiled surfaces:* One 250 ml bottle of Betonit Grout Sealer will cover approximately 12.5 square meters of grouted area. Consumption may vary depending on width and porosity of grout.
- *For masonry surface:* One 250ml bottle will cover approximately 1/4 square meters (1 m<sup>2</sup>/L per coat)

## Instructions:

### SURFACE PREPARATION:

*Tile grout or masonry surface must be fully cured, clean and free from standing water, surface dirt, dust, loose materials, oils and other contaminants.*

### APPLICATION:

1. *Apply Grout Sealer at least 12 hours after grouting.*
2. *Apply using a bristle brush, preferably just a little wider than the grout line for maximum coverage. Repeat application until the substrate remains moist for a few minutes. On vertical applications, apply the material from the bottom up.*
3. *Allow 24 hours curing time before exposure to water or foot traffic for maximum sealing performance.*

### HANDLING:

*Wear protection for eyes and skin such as goggles, gloves and boots. Keep cap on bottle when not in use. Store in a cool, dry place.*

### PRECAUTIONS:

*Avoid direct skin and eye contact. If in contact with skin or eyes, flush immediately with water for at least 15 mins and obtain medical attention. Keep out of reach of children.*

### FOR BEST RESULTS...

*Make sure that the surface is fully cured, clean and dry prior to applying protector.*

*A test application is necessary on surface to be treated to ensure compatibility and the desired results.*

**Grout Sealer Liquid is OPAQUE WHITE. This will not affect the color of the grout. Freshly applied grout sealer may exhibit paling of colors, however, when grout sealer has fully cured, grout will return to its full natural color.**

## Availability

Betonit Grout Sealer and other Betonit products are widely distributed. For dealer information, call us at Betonit Products (Phils) Inc., ☎ (63-2) 932-8806 or (63-2) 931-3822